



ARDEX AF 266

Outdoor Grass Carpet Adhesive

Water based - Safe indoor/outdoor installation

Long working time - Perfect for large installations

Strong initial grab - Reduces edge curl

Excellent trowelability - Easy to trowel and use

ARDEX Australia Pty Ltd
20 Powers Road
Seven Hills NSW 2147
Tel: (02) 9851 9199
Fax: (02) 9674 5621
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX New Zealand Ltd
32 Lane St, Woolston
Christchurch, New Zealand
Tel: (03) 384 3029
Fax: (03) 384 9779
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX AF 266

Outdoor Grass Carpet Adhesive

SPECIAL PROPERTIES

- Water based
- Extremely high strength
- Long working time
- Versatile – roughened fibreglass, aluminum and marine ply
- Resistant to frequent heavy commercial cleaning
- Low odour

PRODUCT DESCRIPTION

Outdoor and Indoor water based outdoor grass and heavy duty indoor carpet adhesive.

Not for permanent saturated areas or areas subject to water ponding.

APPLICATION

External and Internal permanent installation.

FLOOR COVERINGS

- Grass Carpet
- Commercial sheet carpet

IN THE ARDEX SYSTEM

To ensure enhanced performance, reliability and warranty always use ARDEX adhesives within SYSTEMARDEX. Other SYSTEMARDEX products include:

- ARDEX Moisture Barrier
- ARDEX Concrete Sealer
- ARDEX Substrate Primers
- ARDEX Self Levelling and Smoothing Compounds
- ARDEX Finishing Compounds

SURFACE PREPARATION

All substrates must comply with AS1884. In particular, it must be level, protected from moisture, firm, load-bearing, free from curing compounds, cracks and also have a high tensile and compressive strength and must be prepared accordingly.

SUBSTRATE BONDING GUIDE

- Hardboard underlayment board approved to AS2458
- Carpet pad underlay
- Cementitious underlayment
- Dry concrete where there is less than 5.5% moisture content or 70% RH.

Contact ARDEX Technical Services for other substrates including terrazzo, ceramic tiles and metal substrates.

DIRECTIONS FOR USE

Refer to carpet manufacturers instructions. Condition adhesive and floor coverings to room temperature 24 hours prior to and 48 hours after installation.

Installation temperature of working area and substrate to be a minimum of 10°C and a maximum of 30°C.

Apply evenly to a suitably prepared substrate using a 3.2 mm V3 trowel. Avoid concentrations of adhesive. Install carpet immediately into wet adhesive. Cut, fit and reposition carpet within 60 minutes. Roll the carpet in both directions with

suitable roller as per manufacturer's recommendation to ensure 100% adhesive transfer. Stiff carpets should be rerolled after 2 hours.

Full strength developed over 24 - 48 hours. Do not expose to heavy traffic within 48 hours.

In internal applications do not expose to water from cleaning or other source for 48 hours.

SPECIAL INSTALLATION INSTRUCTION

For external applications adhesive is water resistant after 5 days. Protect from water for five days after installation.

NOTE: Do not reuse container. Dispose of container and adhesive residue in accordance with Federal, State and Local waste disposal regulations. Do not flush adhesive down drains.

SAFETY PRECAUTIONS

CAUTION: IRRITANT.

Avoid eye and skin contact. If eye contact occurs, flush with water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Keep container closed.

KEEP OUT OF REACH OF CHILDREN.


CAUTION:

Initially there may be a potential adverse impact on indoor air quality within the general work area during the installation process. During the installation process, adequate ventilation of the work area should be maintained without causing the entry of contaminants to other parts of building. Persons who are sensitive to odours and/or chemicals should avoid the work area.

Material safety datasheets available upon request, available from the ARDEX website www.ardex.com or from point of sale.

TECHNICAL PROPERTIES

- Colour:** Off white
- Priming:** If required prime porous substrate with ARDEX P51
- Coverage:** Using 3.2mm V3 trowel approx 2m²/L



Open Time: Wet set install immediately

Working Time: 60 minutes varying on substrate, temperature and humidity

Site Variability: Site conditions including porosity, temperature and humidity will alter coverage, tack and working time

Packaging: 15 Litre pail containing 18kg of adhesive

Removal: Wet Clean with warm soapy water

Dry Clean with mineral spirits carefully following warnings on container.

Shelf Life: One year from date of manufacture in unopened container stored at 23°C with less than 50% RH

ARDEX Australia Pty Ltd

NSW Ph (02) 9851 9100 Fax (02) 9838 7970
QLD Ph (07) 3817 6000 Fax (07) 3881 3188
VIC/TAS Ph (03) 9308 9255 Fax (03) 9308 9332
SA Ph (08) 8268 2511 Fax (08) 8345 3207
WA Ph (08) 9256 8600 Fax (08) 9455 1227

ARDEX New Zealand Ltd

Christchurch Ph (03) 3843 029 Fax (03) 3849 779
Auckland Ph (09) 2967 690 Fax (09) 2967 689
Wellington Ph (04) 5685 949 Fax (04) 5686 376

Technical Services Toll Free: 1800 224 070

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

© ARDEX Australia Pty Ltd 2008.

All aforementioned products are the trade marks of ARDEX Australia Pty Ltd, its licensors and affiliates.