



ARDEX AF 360

Decoupling Mat Adhesive

For use with ARDEX DS60 Decoupling mat

Completely Washable

Water Based - Cleans up with water

Solvent Free - Low VOC and user friendly

ARDEX Australia Pty Ltd
20 Powers Road
Seven Hills NSW 2147
Tel: (02) 9851 9199
Fax: (02) 9674 5621
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX New Zealand Ltd
32 Lane St, Woolston
Christchurch, New Zealand
Tel: (03) 384 3029
Fax: (03) 384 9779
Email: techinfo@ardexaustralia.com
Internet: www.ardex.com

ARDEX AF 360

Decoupling Mat Adhesive

PRODUCT DESCRIPTION

ARDEX AF 360 is a temporary adhesive, that assists the installation of the decoupling mat, and upon removal is water washable.

It is a water based adhesive free of hazardous organic compounds. For use with ARDEX DS60 Decoupling Mat.

DIRECTIONS FOR USE

Refer to ARDEX DS60 Decoupling Mat Datasheet for further instructions on the decoupling system.

Condition adhesive and ARDEX DS60 Decoupling Mat to working area temperature 24 hours prior to and 48 hours after installation.

Installation temperature of working area and substrate to be a minimum of 10°C and a maximum of 30°C.

Allow the adhesive 'setup' approximately 15-25 minutes. Setup and Working time will vary based on job conditions, substrate, temperature and humidity.

Apply evenly using a roller. Avoid concentrations of adhesive. Fit and install ARDEX DS60 Butynol Decoupling Mat into position accordingly. Roll the flooring in both directions using the recommended roller (normally 35-50kg). Tiling may begin after 30 minutes.

TO REMOVE

Soak the cured adhesive with warm water for 10-20 minutes, then using a stiff brush or scouring pad remove adhesive from substrate.

Installation temperature of working area and substrate to be a minimum of 10°C and a maximum of 30°C.

NOTE: Do not reuse container. Dispose of container and adhesive residue in accordance with Federal, State and Local waste disposal regulations. Do not flush adhesive down drains.

PACKAGING

ARDEX AF360 is available in a 18kg (15l) pail.

COVERAGE

18kg (15L) of ARDEX AF360 is sufficient for approximately 100m², that is 7-8m²/L. The coverage will vary depending on substrate condition and application technique.

Please note:

If there is concerns over the sensitivity of the substrate, it is advised to complete a test patch prior to application and/or contact ARDEX Technical Services for advice.

SAFETY PRECAUTIONS

CAUTION:

Avoid eye and skin contact. If eye contact occurs, flush with water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed, do not induce vomiting. Call physician immediately. Keep container closed.

KEEP OUT OF REACH OF CHILDREN.

Material safety datasheet available upon request, available from the ARDEX website www.ardexaustralia.com or from point of sale.

ARDEX Australia Pty Ltd

Technical Services Toll Free: 1800 224 070

NSW	Ph (02) 9851 9100	Fax (02) 9838 7970
QLD	Ph (07) 3817 6000	Fax (07) 3881 3188
VIC/TAS	Ph (03) 9308 9255	Fax (03) 9308 9332
SA	Ph (08) 8268 2511	Fax (08) 8345 3207
WA	Ph (08) 9256 8600	Fax (08) 9455 1227

ARDEX New Zealand Ltd

Technical Services Toll Free: 0800 227 339

Auckland	Ph (09) 2967 690	Fax (09) 2967 689
Wellington	Ph (04) 5685 949	Fax (04) 5686 376
Christchurch	Ph (03) 3736 900	Fax (03) 3849 779

DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

© ARDEX Australia Pty Ltd 2010.

All aforementioned products are the trade marks of ARDEX Australia Pty Ltd, its licensors and affiliates.